

नेपाल सरकार कृषि तथा मुश्री विकास मन्त्रालय कृषि तथा मुश्री विकास मन्त्रालय कृषि तथा मुश्री विकास मन्त्रालय प्रियोजना कार्यान्वसम् एकाइ कार्युजना कृषि याकितकरण सम्बन्धित सामाग्रीहरु कृषि याकितकरण सम्बन्धित सामाग्रीहरु

आ.व. २०८१/८२

			कास्त्री			आ.व. २०८१/१
S. N.	Name of Farm machinery & Equipments	Technical Specification	Proposed Specification by Suppliers	Rate (include vat for applicable items)	Rate in Word	Remarks
		Mini tiller not less than 4.4kw ± 0.2Kw capacity with manual or electric start, having 4 stroke Petrol engine with air cooled cooling system, A set of rotary rotavator/cultivators attached having minimum of 24 blades and covering minimum of 800-900 mm tilling width and minimum of 100 mm tilling depth, Gear and chain system power transmission with manual shifting of 1- reverse, 2-forward, Verified engine test report should be provided Mini tiller not less than 6kw ± 0.2Kw capacity with manual or electric start, having 4 stroke Petrol engine with air cooled cooling system, A set of rotary rotavator/cultivators attached having minimum of 32 blades and covering minimum of 1000 mm tilling width and minimum of 100 mm tilling depth, Gear	Make and Model Country of Origin			
			Proposed Specification			
1 1	Mini		Offered Services if any			
	Tiller (suitable		Stock Quantity in number			
	for multipurpo		Make and Model			
	se farm work)		Country of Origin			
			Proposed Specification			
			Offered Services if any			उपकरणको
		report salvata de protincia	Stock Quantity in number			फोटो, उपकरणको specificatio
1		Mini tiller not less than 3.7kw ± 0.2Kw capacity with manual or electric start, having 4 stroke Diesel engine with air cooled cooling system, A set of rotary rotavator/cultivators attached having minimum of 24 blades and covering minimum of 800-900 mm tilling width and minimum of 100 mm tilling depth, Gear and chain system power transmission with manual shifting of 1- reverse, 2-forward	Make and Model			खुल्ने catalo leaflets आर् समेत पेश
			Country of Origin			गर्नुपर्नेछ
			Proposed Specification			
			Offered Services if any			
			Stock Quantity in number			
			Make and Model	Tung.		
		Mini tiller not less than 4.4kw ± 0.2Kw capacity with manual or electric start, having 4 stroke Diesel engine with air cooled cooling system, A set of rotary	Country of Origin			
		rotavator/cultivators attached having minimum of 24 blades and covering minimum of 800-900 mm tilling	Proposed Specification			
		width and minimum of 100 mm tilling depth, Gear and chain system power transmission with manual shifting of 1- reverse, 2-forward, Verified engine test report should be provided	Offered Services if any			
		Topon savane vo promoto	Stock Quantity in number			
			Make and Model			
		Mini tiller not less than 6kw ± 0.2Kw capacity with manual or electric start, having 4 stroke Diesel engine with air cooled cooling system, A set of rotary	Country of Origin			
		rotavator/cultivators attached having minimum of 32 blades and covering minimum of 1000 mm tilling width and minimum of 100 mm tilling death. Gear	Proposed Specification			
	width and minimum of 100 mm tilling depth, Gear and chain system power transmission with manual shifting of 1- reverse, 2-forward, Verified engine test	and chain system power transmission with manual	Offered Services if any			
		report should be provided	Stock Quantity in number			

माधव प्रसाद लाक्सादा



नेपाखध्सरकार कृषि तथा पश्चिपद्धी विकास मन्त्रालय कृषि प्रातिकार्य प्रमाणिका परियोजना क्रियान्त्रम् क्रियान्त्रम् क्रियान्त्रम् क्रियान्त्रम् क्रियान्त्रम् क्रियान्त्रम् क्रियान्त्रम् क्रियान्त्रम् विकास्य व्यातिकार्यस्य क्रियान्त्रम् व्यातिकार्यस्य क्रियान्त्रम् व्यातिकार्यस्य क्रियान्त्रम् व्याप्तिकार्यस्य क्रियान्त्रम् व्याप्तिकार्यस्य क्रियान्त्रम् व्याप्तिकार्यस्य क्रियान्त्रम् व्याप्तिकार्यस्य क्रियान्त्रम् व्याप्तिकार्यस्य क्रियान्त्रम् व्याप्तिकार्यस्य क्रियान्त्रम् व्याप्तिकार्यस्य

आ.व. २०८१/८२

ame of arm nachinery	Technical Specification	Proposed Specification by Suppliers	Rate (include vat for applicable items)	Rate in Word	Remarks
quipments	Power tiller not less than 13.4 kw ± 0.2Kw capacity, having 4 stroke diesel engine and radiator/hopper water Cooling system, Minimum ground clearance	Make and Model			
	having minimum of 24 blades and covering minimum of 800-900 mm tilling width, Gear and chain system power transmission with manual shifting, 1- reverse, 3-forward (both high and low) numbers of gears,	Proposed Specification			
Power Tiller (suitable for	Verified engine test report should be provided	Offered Services if any			
		Stock Quantity in number			
se farm	having 4 stroke diesel engine and radiator/hopper	Make and Model			
work	185 mm. A set of rotary tiller / cultivators attached having minimum of 24 blades and covering minimum	Country of Origin			
	power transmission with manual shifting, 1- reverse, 3- forward (both high and low) numbers of gears,	Proposed Specification			
	Verified engine test report should be provided	Offered Services if any			
		Stock Quantity in number			
	Power Weeder of 4 stroke Petrol Engine not less than 2.2kw ± 0.2kw or 50cc capacity, overall cultivation width-adjustable or (300-600). Rated engine speed	Make and Model			
	not less than 1000 RPM (preferred), power transmission gear type with forward gear arrangement,	Country of Origin			
	Verified engine test report should be provided	Proposed Specification			
		Offered Services if any			
Power		Stock Quantity in number			उपकरणको फोटो, उपकरणको क्रक्टाज्जांज बुल्ने
Weeder	1.5kw ± 0.2Kw capacity, overall cultivation width-	Make and Model			catalogs, leaflets आदि समेत पेत मर्नुपर्नेष्ठ
	RPM (preferred), power transmission with manual shifting of 1- reverse, 2-forward, Verified engine test	Country of Origin			
	report should be provided	Proposed Specification			
		Offered Services if any			
		Stock Quantity in number			
	2 stroke/4 stroke Petrol engine operated Portable Electric High Pressure Power Sprayer having power not less than 2kw ± 0.2Kw, provided with minimum	Make and Model			
	of 30m length high quality hose pipe with rolling arrangement, recommended working pressure of 1.5-2.5 Mpa supported with spray lance and nozzle with	Country of Origin Proposed Specification			
	vertical range above 10 mtr and flowrate not less than 10ltr/min				
		Only out vives it ally			
(n	Power Tiller (suitable for nultipurpo se farm work)	Power tiller not less than 13.4 kw ± 0.2Kw capacity, having 4 stroke diesel engine and radiator/hopper water Cooling system, Minimum ground clearance 185 mm. A set of rotary tiller / cultivators attached having minimum of 24 blades and covering minimum of 800-900 mm tilling width, Gear and chain system power transmission with manual shifting, 1- reverse, 3-forward (both high and low) numbers of gears, Verified engine test report should be provided Power tiller not less than 15 kw ± 0.2Kw capacity, having 4 stroke diesel engine and radiator/hopper water Cooling system, Minimum ground clearance 185 mm. A set of rotary tiller / cultivators attached having minimum of 24 blades and covering minimum of 800-900 mm tilling width, Gear and chain system power transmission with manual shifting, 1- reverse, 3-forward (both high and low) numbers of gears, Verified engine test report should be provided Power Weeder of 4 stroke Petrol Engine not less than 2.2kw ± 0.2kw or 50cc capacity, overall cultivation width-adjustable or (300-600), Rated engine speed not less than 1000 RPM (preferred), power transmission gear type with forward gear arrangement, Verified engine test report should be provided Power Weeder of 2 stroke Petrol Engine not less than 1.5kw ± 0.2kw capacity, overall cultivation width-adjustable or (600-900), Rated engine speed and less than 1000 RPM (preferred), power transmission with manual shifting of 1- reverse, 2-forward, Verified engine test report should be provided Power Weeder of 2 stroke Petrol Engine not less than 1.5kw ± 0.2kw capacity, overall cultivation width-adjustable or (600-900), Rated engine speed 3600 RPM (preferred), power transmission with manual shifting of 1- reverse, 2-forward, Verified engine test report should be provided Power Weeder of 2 stroke Petrol Engine not less than 1.5kw ± 0.2kw, provided with minimum of 30m length high quality hose pipe with rolling arrangement, recommended working pressure of 1.5-2.5 Mpa supported with spray lance and nozzle with vertical	Power tiller not less than 13.4 kw ± 0.2Kw capacity . having 4 stroke diesel engine and radiator/hopper water Cooling system, Minimum ground clearance 185 mm. A set of rotary tiller / cultivators attached having minimum of 24 blades and covering minimum of 800-900 mm tilling width, Gear and chain system power transmission with manual shifting, 1 - reverse, 3- forward (both high and low) numbers of gears, Verified engine test report should be provided Power tiller not less than 15 kw ± 0.2Kw capacity . having 4 stroke diesel engine and radiator/hopper water Cooling system, Minimum ground clearance 185 mm. A set of rotary tiller / cultivators attached having minimum of 24 blades and covering minimum of 800-900 mm tilling width, Gear and chain system power transmission with manual shifting, 1 - reverse, 3- forward (both high and low) numbers of gears, Verified engine test report should be provided Power Weeder of 4 stroke Petrol Engine not less than 2.2kw ± 0.2Kw or 50ce capacity, overall cultivation width-adjustable or (300-600), Rated engine speed not less than 1000 RPM (preferred), power transmission gear type with forward gear arrangement, Verified engine test report should be provided Power Weeder of 2 stroke Petrol Engine not less than 1.5kw ± 0.2Kw capacity, overall cultivation width-adjustable or (600-900). Rated engine speed not less than 1000 RPM (preferred), power transmission gear type with forward gear arrangement, Verified engine test report should be provided Power Weeder of 2 stroke Petrol Engine not less than 1.5kw ± 0.2Kw capacity, overall cultivation width-adjustable or (600-900). Rated engine speed afoon RPM (preferred), power transmission with manual shifting of 1 - reverse, 2-forward, Verified engine test report should be provided Power Weeder of 2 stroke Petrol Engine not less than 1.5kw ± 0.2Kw, provided with minimum of 300 net length high quality hose pipe with rolling arrangement, recommended working pressure of 1.5-2.5 Mpa supported with spray lance and nozzle with vertical range ab	Power tiller not less than 13.4 kw ± 0.2 kw capacity having 4 stroke diesel engine and radiator/hopper water Cooling system, Minimum ground clearance 185 mm. A set of rotary tiller / cultivators attached having minimum of 24 blades and covering minimum of 300-900 mm tilling width, Gear and chain system power transmission with manual shifting, 1 - reverse, 3 forward (both high and low) numbers of gears, Verified engine test report should be provided Power tiller not less than 15 kw ± 0.2 kw capacity having 4 stroke diesel engine and radiator/hopper water Cooling system, Minimum ground clearance of the cool of the provided water of 300-900 mm tilling width, Gear and chain system power transmission with manual shifting, 1 - reverse, 3 forward (both high and low) numbers of gears, Verified engine test report should be provided Power Weeder of 4 stroke Petrol Engine not less than 2 kw ± 0.2 kw ± 0.2 kw ± 0.2 kw to 500-600, Rated engine speed not less than 1000 RPM (preferred), power transmission gear type with forward gear arrangement, Verified engine test report should be provided Power Weeder of 2 stroke Petrol Engine not less than 1.5 kw ± 0.2 kw expacity, overall cultivation width-adjustable or (500-900). Rated engine speed not less than 1000 RPM (preferred), power transmission gear type with forward gear arrangement, Verified engine test report should be provided Power Weeder of 2 stroke Petrol Engine not less than 1.5 kw ± 0.2 kw expacity, overall cultivation width-adjustable or (500-900). Rated engine speed soon RPM (preferred), power transmission with manual shifting of 1 - reverse, 2-forward, Verified engine test report should be provided Power Weeder of 2 stroke Petrol Engine not less than 1.5 kw ± 0.2 kw expacity, overall cultivation width-adjustable or (500-900). Rated engine speed soon RPM (preferred), power transmission with manual shifting of 1 - reverse, 2-forward, Verified engine test report should be provided Power Weeder of 2 stroke Petrol engine operated Portable Electric Hi	achiery Power Uller not less than 13.4 kw ± 0.2Kw capacity, having 4 stroke diesel engine and radiatorhopper water Cooling system, Minimum ground clearance 185 mm. A set of rotary tiller (cathievare attachmony of the control of th

माधव प्रसाद लंकसाव



नेपाल सरकार कृषि तथा पर्मासी विकास भन्तालय प्रमासी कृषि साम्रोनकीकरण परियोजना परियोजनी कृषि साम्रोनकीकरण परियोजना परियोजनी कार्योजना एकाइत कास्की

आ.व. २०८१/८२

			कारकी		आ	.व. २०८१/८
	Name of Farm machinery & Equipments	Technical Specification	Proposed Specification by Suppliers	Rate (include vat for applicable items)	Rate in Word	Remarks
0.00	Sprayer	Single phase Portable Electric High Pressure Power Sprayer having not less than 1Kw electric power, 1400 rpm provided with minimum of 30m length high	Make and Model			
		quality hose pipe with rolling arrangement, recommended working pressure of 1.5-2.5 Mpa supported with spray lance and nozzle	Country of Origin			
		,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,	Proposed Specification			
			Offered Services if any			
		Chain saw 2 stroke Petrol Operated	Stock Quantity in number			
		Bar length 18 inch to 24-inch, Power not less than 70 cc, minimum sound pressure level will be preferred	Make and Model Country of Origin			
5	GI . G		Proposed Specification			
,	Chain Saw	n Saw	Offered Services if any			
			Stock Quantity in number			
		Brush Cutter 4 stroke Petrol Engine (Back pack/side pack)	Make and Model			
		Power not less than 31cc, minimum 3T/40T/80T/nylon trimmer blade	Country of Origin			
			Proposed Specification			
			Offered Services if any			
6	Brush		Stock Quantity in number			
	cutter	Brush Cutter 2 stroke Petrol Engine (Back pack/side pack)	Make and Model			
		Power 40cc up to 55cc, minimum 3T/40T/80T/nylon trimmer blade	Country of Origin			
			Proposed Specification			
			Offered Services if any			
			Stock Quantity in number			
		Petrol water Pump of self-priming with 2-inch to 3- inch outlet and inlet, minimum 5 hp engine power, suction head not less than 7mtr and delivery head not	Make and Model			
		less than 20 mtr.	Country of Origin			
7	Petrol water Pump		Proposed Specification			
			Offered Services if any			
			Stock Quantity in number			

जाराव प्रसाद कृषि अधिकृष



	Name of					1230
N.	Farm machinery & Equipments	Technical Specification	Proposed Specification by Suppliers	Rate (include vat for applicable items)	Rate in Word	Remarks
		2 in 1 manual cum Battery operated knapsack sprayer Battery-12V, 8A or 12V 12A, Working Pressure-0.10 to 0.45 megapascal, Volume not less than 16-liter,	Make and Model Country of Origin			
8	Battery cum manaul	Trigger Type brass is preferred	Proposed Specification			उपकरणको फोटो, उपकरणको specification खुल्ले
	Sprayer (2in1)		Offered Services if any			catalogs, leasles अगर्र समेत पेश गर्नुपर्नेड
			Stock Quantity in number			
			Make and Model			
			Country of Origin			
9	Pit Digger/Ear th Auger		Proposed Specification			
			Offered Services if any			
			Stock Quantity in number			
		Digital Weighing Machine of Capacity 50 kg Loaded with Rechargeable Battery, Large LED Display on	Make and Model			
		Top that can be read easily, material Stainless Steel (preferred), High Precision Load Cell, Auto calibration facility with standard weigh	Country of Origin			
			Proposed Specification			
			Offered Services if any			
10	Digital		Stock Quantity in number			
10	Weighing Machine	Digital Weighing Machine of Capacity 100 kg, Loaded with Rechargeable Battery, Large LED	Make and Model			
		Display on Top that can be read easily, material Stainless Steel (preferred), High Precision Load Cell, Auto calibration facility with standard weigh	Country of Origin			
			Proposed Specification			
			Offered Services if any			
			Stock Quantity in number			

Manufacture company or suppliers strictly provided engine rated power of power tiller and mini tillier in "Kw" this should be mentioned in both catalogue and

Tools:-A set of tools as required for general maintenance shall be supplied.

Warranty:-Manufacturer shall provide at least one year of warranty.

Delivery:- All items must be delivered to locations within Pokhara Valley.

Stocks:-Must be capable of meeting required demand quantities.

Initial Service:-The supplier shall provide all the necessary filters, engine oil, gear oil and spare parts required for the operations of machine.

Training:- For all the farm machinery training for Operator and General maintenance training shall be provided by suppliers

Installation and Commissioning:-Supplier must accomplish proper installation and commissioning on site.

Certification: - Lab certificate regarding machineries power with respected country verified certification must be provided by suppliers.

*The major items are indicated by bold and highlighted letters/alphabets/figures in the technical specifications.

Approved By

नाधव प्रसाद लान्साल बरिष्ठ कृषि अधिकृत





बा.व. २०८९/८२

कृषि उपकरण सम्बन्धित सामाग्रीहरू

s.n.	Name of Farm machinery & Equipments	Technical Specification	Proposed Specification by Suppliers	Rate (include vat for applicable items)	Rate in Word	Remarks
			Make and Model			4-17
1		of blades not less than 32 (or most available), main	Country of Origin			
	Rotavator (Tractor Drawn)		Proposed Specification			
			Offered Services if any			
			Stock Quantity in number			
		more than 35 HP Tractor Drawn spring tynes cultivator with overall tilling width not less than 5 feet made up of heavy duty frame, Number of tynes not less than 9 (or most available), tyne type reversible shovel type, Hitching 3-point linkage	Make and Model			
	Cultivator		Country of Origin			उपकरणको फोटो.
2			Proposed Specification			उपकरणको उपकरणको specification खुल्ले calalogs, leaflets आदि समेत पेश गर्नुपर्नेछ।
			Offered Services if any			
			Stock Quantity in number			
			Make and Model			
		manually row to row distance adjustable, minimum of 150 grams per seed box, seed rate can be controlled manually, Light in weight, easy handeling	Country of Origin			
3	Manual seeder for vegatable	and repairing, mostly designed for onion, beetroot, carrot, raddish, coriander etc., should cover the land	Proposed Specification			
		after seeding, most provide all the tools and disc required, arrangement for seed depth adjustment, minimum of 4 rows	Offered Services if any			
			Stock Quantity in number			

Manufacture company or suppliers strictly provided engine rated power of power tiller and mini tillier in " Kw " this should be mentioned in both catalogue and Instruments otherwise these company and suppliers or materials should be disqualified or rejected.

Tools:-A set of tools as required for general maintenance shall be supplied.

Warranty:-Manufacturer shall provide at least one year of warranty.

Delivery:- All items must be delivered to locations within Pokhara Valley.

Stocks:-Must be capable of meeting required demand quantities.

Initial Service:-The supplier shall provide all the necessary filters, engine oil, gear oil and spare parts required for the operations of machine.

Training:- For All the farm machinery training for Operator and General maintenance training shall be provided by suppliers

Installation and Commissioning:-Supplier must accomplish proper installation and commissioning on site.

Certification:- Lab certificate regarding machineries power with respected country verified certification must be provided by suppliers.

*The major items are indicated by bold and highlighted letters/alphabets/figures in the technical specifications.

Approved By

STEED VETTE CHARACT



						२०८१/८२
s.N.	Name of Farm machinery & Equipments	Technical Specification	Proposed Specification by Suppliers	Rate (include vat for applicable items)	Rate in Word	Remarks
			Make and Model		Subarra Nilah Malama Aga Na	
		Main body made up of stainless steel with sealing mode in centre and in 3 side, can sealed Polyethylene (PE), Polypropylene (PP) and Laminations with	Country of Origin			
1	Rand seeler	motorized rubber conveyer with speed control capable of speed up to 12 mtr/min and customizable,	Proposed Specification			
		horizontal module having conveyer height 110mm- 254mm, motor capacity 600 to 1500 watt, single phase 220V/50Hz electric operated with temperature range from 0 to 300 deg.celsius	Offered Services if any			
			Stock Quantity in number			
			Make and Model			
			Make and Model			
	Impulse	, , , , , , , , , , , , , , , , , , ,	Country of Origin			
2			Proposed Specification			
			Offered Services if any			
			Stock Quantity in number			
		Combined Rice Mill must remove paddy husk,	Make and Model			
		whitening rice, crush rice bran at one time, it must attached with alloy-steel roller that the rice has low breakage after processed, body material: High quality steel, Capacity: rice mill not less than 80Kg/hr, pulverizer not less than 150kg/hr, Mill type: Disc/Hammer, Splindle speed: 1200R/M (rice milling), Motor Power: 2.2kw ± 0.2 kw, single phase, 50 Hz with 100% copper wire binding motor, milled rate	Country of Origin			
3	Combined Rice Mill		Proposed Specification			
			Offered Services if any			
		not less than 75%, must be applicable in both milling of cereals such as rice, wheat, millet etc.	Stock Quantity in number			
		Hygenic Food grade approved, Milk cans must made caring hygienic point of view giving mirror polish, SS	Make and Model			
		304 Milk Can, 20/30/40 Ltr Capacity, weight not less than 7kg	Country of Origin			
4	Milk Can		Proposed Specification			
			Offered Services if any			
			Stock Quantity in number			

माधव प्रसादि लक्सावा



S.N.	Name of Farm machinery & Equipments	Technical Specification	Proposed Specification by Suppliers	Rate (include vat for applicable items)	Rate in Word	Remarks
	Equipments	Heavy duty interlocking or non interlocking high quality rubber cow mat having Size 7*4 feet and 6*4 feet, thickness not less than 17mm, weight not less than 36kg	Make and Model Country of Origin			
5	Cow Mat		Proposed Specification			
			Offered Services if any			
		Conveying type electric chaff cutter having Single	Stock Quantity in number			
		phase high quality electric motor, power output not less than 2.2 ± 2 Hp electric motor with 220V, motor speed not less than 2000 rpm, shall fully equiped with	Make and Model Country of Origin			
6	Chaff Cutter	accessories for efficient full load operation of chaff cutter along with safety features, number of blade at least 2, mild steel frame structure, capacity not less than 600 kg/h, can be used for green grass, straw	Proposed Specification			
,			Offered Services if any			
		Eunstians: Display Fat Solids not Fats(SNF) added	Stock Quantity in number			
7	Milk Analyser	Functions: Display Fat, Solids-not-Fats(SNF), added, water, added additives, Measurement Parameters: a) Fat Range:0-10% Resolution:0.1% Accuracy: ±0.1% (b) SNF Range:4-10% Resolution:0.2% Accuracy:0.2% (c) Added Water Range:0-100% Resolution:0.1% Accuracy: ±0.1%, Measuring Time: 30 seconds or less, Milk Sample: 25ml or less, Display: 2 line 20 character, Operating Voltage 220-240 V, single Phase,50 Hz, DC input 12V, Software: Software for automatic collection of information from analyzer and weighing Scale, multi windows running,saving data, prepare farmer's milk procurement and other accounting transactions, Software: Software for automatic collection of information from analyzer and weighing Scale, multi windows running,saving data, prepare farmer's milk procurement and other accounting transactions	Make and Model Country of Origin Proposed Specification Offered Services if any Stock Quantity in number			उपकरणको फोटो, उपकरणको specification खुल्ले catalogs, leaflets সাহি নাসন সাহ দাবি দাবি দাবি দাবি দাবি দাবি

माधव प्रसाद लाक्साल





S.N.	Name of Farm machinery & Equipments	Technical Specification	Proposed Specification by Suppliers	Rate (include vat for applicable items)	Rate in Word	Remarks
8	Chilling Vat 500 Ltr	Cooling Capacity: 500 Itrs of milk from 35°C to 4°C in 4 hours time, Material of Fabrication: SS 304 Grade, Thickness of SS Sheet: a) Inner Thickness 1.5-2mm b)Outer Thickness 1.2-1.6 mm Shape of Chilling Vat: Rectangular/Circular/Elleptical, Electric Supply Single or Three Phase with Agitator 28-40 Rpm with motor, gear box, SS shaft and blades, Insulation 75mm or more thick PUF insulation, temperature increase <2°C/24 hr, Outlet Valve: 1.5 inch(38mm), Butterfly Valve, Cover for Chilling Vat: SS Cover Cooling System: Direct expansion Type Refrigerant: R404a/134a/407c, Compressor: at least 2 ton Capacity, 1 number hermetic compressor, Condenser: Air cooled Condenser with expansion Valve, Filter Dryer, liquid receiver, etc., Evaporator/Cooling unit: Dimple plate type, Control Panel: Dust and Moisture proof Tank/Wall mounted electronic control panel, Manual and Auto mode operation, MCB, Contractors, Overload Relays, electronic thermostat with indicator, HPLP switch, etc., Milk Volume Measurement: At least 20-25 lit graduation SS dip stick	Make and Model Country of Origin Proposed Specification Offered Services if any Stock Quantity in number			
9	Chilling Vat 1000 Ltr	Cooling Capacity: 1000 ltrs of milk from 35°C to 4°C in 4 hours time, Material of Fabrication: SS 304 Grade, Thickness of SS Sheet: a) Inner Thickness 1.5- 2mm b)Outer Thickness 1.2-1.6 mm Shape of Chilling Vat: Rectangular/Circular/Elleptical, Electric Supply Single or Three Phase with Agitator 28-40 Rpm with motor, gear box, SS shaft and blades, Insulation 75mm or more thick PUF insulation, temperature increase <2°C/24 hr, Outlet Valve: 1.5 inch(38mm), Butterfly Valve, Cover for Chilling Vat: SS Cover Cooling System: Direct expansion Type Refrigerant: R404a/134a/407c, Compressor: at least 2 ton Capacity, 2 number hermetic compressor, Condenser: Air cooled Condenser with expansion Valve, Filter Dryer, liquid receiver, etc., Evaporator/Cooling unit: Dimple plate type, Control Panel: Dust and Moisture proof Tank/Wall mounted electronic control panel, Manual and Auto mode operation, MCB, Contractors, Overload Relays, electronic thermostat with indicator, HPLP switch, etc., Milk Volume Measurement: At least 20-25 lit graduation SS dip stick	Make and Model Country of Origin Proposed Specification Offered Services if any Stock Quantity in number			

माधव प्रसाद लास्साल



पोस्ट हार्भेस्ट तथा डेरी याम्प्रिकरण सम्बन्धित सामाग्रीहरू

आ.व. २०८१/८२

	Name of Farm			Rate (include vat		(04)/4(
S.N.	machinery & Equipments	Technical Specification	Proposed Specification by Suppliers	for applicable items)	Rate in Word	Remarks
		One wheeled, wheel barrow having two handles and one container, unbreakable iron body, durable metal frame, wheel constructed of mild steel disk type fitted with pneumatic tyres used for variety of things such as disposing manure, fertilizers etc.	Make and Model Country of Origin			
10	Wheel barrow		Proposed Specification			
			Offered Services if any			
			Stock Quantity in number			
		Feed pellet machine having 100% copper binded electric motor with power not less than 2.2kw ± 0.2	Make and Model			
		kw, single phase, operation mode: semi automatic hammer mill type, Build Material: robust CI/ MS build body, capacity not less than 50kg/hr, output pellet	Country of Origin			
11	Animal Feed Pellet Machine	size: 2mm to 6mm provided with required number of die (minimum of 2 No.)	Proposed Specification			
			Offered Services if any			
			Stock Quantity in number			

Manufacture company or suppliers strictly provided engine rated power of power tiller and mini tillier in "Kw" this should be mentioned in both catalogue and Instruments otherwise these company and suppliers or materials should be disqualified or rejected.

Tools:-A set of tools as required for general maintenance shall be supplied.

Warranty:-Manufacturer shall provide at least one year of warranty.

Delivery:- All items must be delivered to locations within Pokhara Valley.

Stocks:-Must be capable of meeting required demand quantities.

Initial Service:-The supplier shall provide all the necessary filters, engine oil, gear oil and spare parts required for the operations of machine.

Training:- For All the farm machinery training for Operator and General maintenance training shall be provided by suppliers

Installation and Commissioning:-Supplier must accomplish proper installation and commissioning on site.

Certification: - Lab certificate regarding machineries power with respected country verified certification must be provided by suppliers.

*The major items are indicated by bold and highlighted letters/alphabets/figures in the technical specifications.

O Patry:

Approved By

WEIG VEHICE THE THE COLD



नेपाल सरकार कृषि तथा पशुपंद्या विकास मन्त्रालय प्रधानम्ध्यारकृषि आधुनिर्काकरण परियोजना परियोजना अधिम्बुसन् प्रसिद्धाः कार्यान्वयन प्रभावना अधिम्बुसन् प्रसिद्धाः कार्यान्वयन प्रसारिटक घर निर्माण सम्बन्धित सामाग्रीहरू

आ.व. २०८१/८२

S.N.	Agricultural Items	Technical Specification	Proposed Specification by Suppliers	Rate (include vat for applicable items)	Rate in Word	Remarks
			Make and Model			
		Greenhouse Polyethylene Plastic	Country of Origin			
		UV stabilized transparent film/diffussed(50-80%) (200	Proposed Specification			
1	UV Plastic 200 micron	microns) Anti-Drip, 5 or 7 layered, Super Strong, Anti Dust (Specify	Weight per sqm			
		the weight and width of plastic sheet available along with lab certification)	Offered Services if any			
			Stock quantity -			
			Make and Model			
		Polyethylene Plastic UV stabilized	Country of Origin			
	UV Plastic	black and white film (200 microns) Anti-Drip, 5 or 7 layered, Super	Proposed Specification			
2	black and white	Strong, Anti Dust (Specify the weight and width of plastic sheet	Weight per sqm			
	a	available along with lab certification)	Offered Services if any			
			Stock quantity -			
			Make and Model			
		Greenhouse Polyethylene Plastic	Country of Origin			
		Plastic Plastic Plastic	Proposed Specification			
3	UV Plastic 100 micron		Weight per sqm			
		plastic sheet available along with lab certification)	Offered Services if any			
			Stock quantity -			
_			Make and Model			THE RES
			Country of Origin			
	Plastic 120	Greenhouse Polyethylene 120 GSM transparent Plastic Sheet	Proposed Specification			
4		with eyelocks (Specify the weight and width of plastic sheet available	Weight per sqf			
	- anoparon	along with lab certification)	Offered Services if any			
			Stock quantity -			

आहात प्रसाद लाक्सादा





		Make and Model
Plastic 120 5 GSM black colour	Greenhouse Polyethylene 120 GSM black Plastic Sheet with eyelocks (Specify the weight and width of plastic sheet available along with lab certification)	Country of Origin Proposed Specification Weight per sqf Offered Services if any
		Stock quantity -
6 Anti Insect Net	UV stabilized White Anti Insect net of mesh size 40, not less than 70 GSM, Non-corrosive, water vapor resistant(Specify the weight and width of net available)	Make and Model Country of Origin Proposed Specification Weight per sqm Offered Services if any Stock quantity -
7 Anti Hail Net	UV stabalized High Density polyethylene (HDPE), transparent White Anti Hail net monofilament leno or rashel knitted type, comprehensive defence against dense hail condition, birds etc. not less than 70 GSM (Specify the weight and width of net available)	Make and Model Country of Origin Proposed Specification Weight per sqm Offered Services if any Stock quantity -
8 Aluminum Profile	PVC coated rust free Zigzag GI wire with polyethylene coating thickness not less than 0.2 mm with 0.8 to 0.9 mm aluminum profile for Greenhouse structures	Make and Model Country of Origin Proposed Specification Offered Services if any Stock quantity -

जाराव प्रसाद लाक्सादा





प्लास्टिक घर निर्माण सैम्बन्धित सामाग्रीहरू

			Make and Model
9	Mulching Plastic	Low Density Polyethylene (LDPE) UV stabilized mulching plastic sheet, thickness not less than 40-micron, colour of sheet white-black/silver-black (Specify the weight and width of net available)	Country of Origin Proposed Specification Offered Services if any Stock quantity -
10	Shade Net	HDPE Shade Net with (50% to 80%) shading capacity with weight not less than 90 GSM, Green in colour, preffered if UV protected. (Specify the weight and width of plastic sheet available)	Make and Model Country of Origin Proposed Specification Weight per sqm Offered Services if any Stock quantity -
11	Plastic 250 GSM	High Density Polyethylene (HDPE) 250 GSM Plastic Sheet for Plastic Pond with standard blue colour(Specify the weight and width of plastic sheet available)	Make and Model Country of Origin Proposed Specification Weight per sqm Offered Services if any Stock quantity -
12	Metal Sprinkler	High quality metal sprinkler having discharge diameter of 20-25 metres with nozzle, stand and connection pipe of size 16-20mm	Make and Model Country of Origin Proposed Specification Offered Services if any Stock quantity -

Delivery:- All items must be delivered to locations within Pokhara Valley.

Stocks:-Must be capable of meeting required demand quantities.

Training:- For All the farm machinery training for Operator and General maintenance training shall be provided by suppliers Installation and Commissioning:-Supplier must accomplish proper installation and commissioning on site.

Certification:- Lab certificate regarding machineries power with respected country verified certification must be provided by suppliers.

*The major items are indicated by bold and highlighted letters/alphabets/figures in the technical specifications.

Approved By



नेपाल सरकार कृषि तथा पशुपंद्धी कियास मन्त्रालय प्रधानमञ्जूषिक के सुनिकीकरण परियोजना परियोजना कार्यान्वयन एक कि


आ.व. २०८१/८२

थोपा सिचाई(Drip Irrigation) तथा रेन पाइप (Rain hose pipe) जडान सम्बन्धित सामाग्रीहरू

S.N.	Agricultural Items	Technical Specification (Size Range)	Proposed Specification by Suppliers	Rate (include vat for applicable items)	Rate in Word	Remarks
1	PVC pipe	50mm to 75mm				
2	GTO with rubber washer	16mm to 20mm				
3	Tape lock joiner	16mm to 20mm				
4	Poly tube	16mm to 20mm				
5	Inline Dripper pipe	16mm to 20 mm with variable spacing from 30cm to 60cm				
6	Emitter	2 litre/hour to 8 litre/hour				
7	Seal Tape					
8	Double lock joiner	16mm to 20mm				
9	Pvc valve / control valve	50mm to 75mm				
10	Flush valve pvc	50mm to 75mm				
11	Elbow pvc	50mm to 75mm				
12	Equal tee	50mm to 75mm				
13	MTA pvc	50mm to 75mm				
14	FTA pvc	50mm to 75mm				
15	Perma Fix- Solvent Cement	litre				
16	Union pvc	50mm to 75mm				

WHERE THE CHOCKING





आ.व. २०८९/८२

थोपा सिचाई(Drip Irrigation) तथा रेन पाइप (Rain hose pipe) जडान सम्बन्धित

	11 111 112 12	mp migation, and an a		ii iiose p		
17	check valve Brass/PVC	50mm to 75mm				
18	Water Filter	Screen/hydrocyclone/sand filter/disc compatible with 50mm to75mm pipe diameter				
19	Gi Nipple	1.5"*4" or usable size				
20	Ventury for fertigation	Set with compatible size				
21	Manifold PVC	50mm to 75mm				
22	Air release valve	32mm to 75mm				
23	End Cap	50mm to 75mm				
24	Coupler	50mm to 75mm				
		Rain Ho	se Pipe			
1	Rainpipe	20mm to 32mm				
2	Ball valve	20mm to 32mm				
3	Rainport MTA	20mm to 32mm				
4	Rainport Joiner	20mm to 32mm				
5	Rainport End cap	20mm to 32mm				
6	PT sleeve	20mm to 32mm			Elm Significan	
7	Service saddle	20mm to 50mm				

Delivery:- All items must be delivered to locations within Pokhara Valley.

Stocks:-Must be capable of meeting required demand quantities.

Training:- For All the farm machinery training for Operator and General maintenance training shall be provided by Installation and Commissioning:-Supplier must accomplish proper installation and commissioning on site.

Certification:- Lab certificate regarding machineries power with respected country verified certification must be

*The major items are indicated by bold and highlighted letters/alphabets/figures in the technical specifications.

Approved By





सिचाईका आवश्यक सामाग्रीहरू

आ.व. २०८१/८२

S.N.	Items	Technical Specification	Capacity	Proposed Specification by Suppliers	Brand Name and country of manufacturing company	Rate (include vat for applicable items)	Rate in Word	Remarks
	PVC Water Tank	Extra Heavy insulated	200 litres					
		polyethylene vertical water storage tanks,triple layer is prefered with proper covering and triple layer is prefered.	500 litres					
			1000 litres					
			1500 litres					
			2000 litres					
1		Confirming to Nepal	3000 litres				11/2	1
		standard or latest modifications. Additional inlet/outlets can be fitted if required.	5000 litres					
2	High	16	PN-16	Not less than				उपकरणको फो
	Density	10	(10Kg/cm²)	0.09				उपकरणको specification
	Polyethyl	20	PN-16	Not less than				खुल्ने catalog
	ene	25	(10Kg/cm ²)	0.13				leaflets आरि समेत पेश
	(HDPE)		PN-16	Not less than				गर्नुपर्नेछ
	Pipe		(10Kg/cm ²) PN-6	0.2 Not less than				
	confirmi	32	(4Kg/cm ²)	0.22				
	ng to	32	PN-10	Not less than				
	Nepal		(6Kg/cm ²)	0.33				
	Standard	40	PN-6	Not less than				
	or latest		(4Kg/cm ²)	0.25				
	modificat	40	PN-10	Not less than				
	ion	-10	(6Kg/cm ²)	0.35				
		40	PN-16	Not less than				
			(10Kg/cm ²) PN-6	0.5				
	1-2-11/2	50		Not less than 0.36				
			(4Kg/cm²) PN-10					
			(6Kg/cm ²)	Not less than 0.54				
			PN-16	Not less than				
		63	(10Kg/cm ²)	0.78				
			PN-6	Not less than				
			(4Kg/cm ²)	0.57				
		63	PN-10 (6Kg/cm ²)	Not less than 0.8				
		63 .	PN-16 (10Kg/cm ²)	Not less than 1.2				
		75	PN-6 (4Kg/cm ²)	Not less than 0.8				

अधिक क्षेत्र अधिकृत





सिचाईका आवश्यक सामाग्रीहरू

आ.व. २०८९/८२

S.N.	Items	Technical Specification	Capacity	Proposed Specification by Suppliers	Brand Name and country of manufacturing company	Rate (include vat for applicable items)	Rate in Word	Remarks
		75	PN-10 (6Kg/cm ²)	Not less than 1.19				
		75	PN-16 (10Kg/cm ²)	Not less than 1.78				
		90	PN-6 (4Kg/cm²)	Not less than 1.22				
		90	PN-10 (6Kg/cm ²)	Not less than 1.7				
		90	PN-16 (10Kg/cm ²)	Not less than 2.58				
		110	PN-6 (4Kg/cm ²)	Not less than 1.7				
		110	PN-10 (6Kg/cm ²)	Not less than 2.5				
		110	PN-16 (10Kg/cm ²)	Not less than 3.8				
	Delivery Cotton Pipe	2 inch						
3		3 inch						
		4 inch						
	PVC Suction Hose Pipe (Hard)	2 inch						
4		3 inch						
4		4 inch						

Delivery:- All items must be delivered to locations within Pokhara Valley.

Stocks:-Must be capable of meeting required demand quantities.

Training:- For All the farm machinery training for Operator and General maintenance training shall be provided by suppliers Installation and Commissioning:-Supplier must accomplish proper installation and commissioning on site.

Certification:- Lab certificate regarding machineries power with respected country verified certification must be provided by suppliers.

*The major items are indicated by bold and highlighted letters/alphabets/figures in the technical specifications.

Approved By

WHEIG THE CHARTER OF THE COLUMN SHEETEN COLUMN SHEETE